PWD FRIENDLY ESTABLISHMENT

The award is given to friendly establishment or building/facilities, wherein the main function of the establishment, must be fully accessible to PWDs, including compliance to all architectural features and facilities within the common areas, as provided to the general public. This also includes accessible areas designated to PWDs (Persons with Disability).

Refer to Rules I, II, and III of the IRR (Implementing Rules and Regulations) of BP 344 (Batas Pambansa Blg. 344).

1). Rule I : "Scope and Application"

2). Rule II : "Minimum Requirements for Accessibility"

3). Rule III : "Specific Requirements For Buildings And Related Structures For

Public Use"

Rule II refers to the required architectural features and facilities as specified for each building type and use, while Rule 3 refers to various building types and use.

Standards and dimensions of the Criteria.

All standards and dimensions of the criteria are based on Rule II of the IRR (implementing rules and regulations) of BP 344 (Batas Pambansa Blg. 344) or otherwise known as the Accessibility Law for PWDs (Persons with Disability). For other dimensions not indicated in the criteria, refer to the IRR of BP 344.

Part I Required Submittals:

Submittals must be in both hard copy and soft copy [CD], and the authorized office to receive these submittals will be PFRD (Philippine Foundation for the Rehabilitation of the Disabled with address at Unit 27, The Columbia Tower, Ortigas Avenue, Mandaluyong City

Criteria

1). Narrative

Write a narrative about the nominated establishment, explaining in 150 words, the type and function of the building/facilities, the demography of the building/facilities, and what considerations had been provided to make the building/facilities accessible to PWDs (Persons With Disability)

2). Floor plan and site development plan

1 | PWD FRIENDLY ESTABLISHMENT 2020

Submittal must provide a reduced size floor plan and site development plan of the establishment or building/facilities. Recommended reduced size of the floor plan or site development plan can either be on A3 sheet for large establishments and on A4 sheet for small establishments. Not-To-Scale floor plans or site development plans are acceptable. In addition, you can delete or block off areas that are not related to your submittal, as long as the route to the accessible facilities are shown

3). Location of Accessible facilities

The floor plan must indicate or highlight the locations of each accessible architectural facilities including appropriate labeling or tagging. These architectural facilities includes, ramps, washroom/toilets/bathrooms for PWDs, reserve parking stalls for PWDs, main doors/entrances, elevators/lifts, telephones / ATMs or Automatic Teller Machines, and all other exterior/interior accessible features and facilities provided to the general public. Refer to the architectural features and facilities of the IRR of BP344 indicated below.

4). Supplemental Photos for each accessible features and facilities

Provide colored photos with proper labels/tagging for each architectural features and facilities of the establishment. Refer to the architectural features and facilities of the IRR of BP344 indicated below. If there are 4 ramps, provide 4 separate photos for each ramp, including reference label/tagging, properly coordinated with the floor plan or site development plan.

5). Submission of Actual detailed dimensions

Provide as part of the attachment, actual dimensions of each accessible features and facilities as shown on the attached form. All dimensions must be in metric system. Dimensions must be based on architectural finishes, unless otherwise indicated.

Example: Accessible ramp

a). handrails.

Handrails must include height dimension from finish floor line to finish top line for upper handrail and finish floor line to finish top line for lower handrail.

Diameter of handrail must also be indicated.

b). clear width of ramp.

Clear width of ramp must indicate the clear distance between the handrails on both sides.

C). Ramp Gradient.

2 | PWD FRIENDLY ESTABLISHMENT 2020

Ramp gradient must include the dimensions of ramp rise and horizontal distance. Gradient = horizontal distance divided by ramp rise.

- d.) Dimensions of Signages.
 dimensions of signages (UN symbol of accessibility) for pavement and upright signages, must be indicated.
- e). And all other architectural features as indicated under ramp of the Architectural Features and Facilities criteria.

The Audit team will verify the actual dimensions as submitted for validation.

Previously Awarded PWD Friendly Establishments

For previously awarded PWD Friendly establishments, these buildings/facilities can be nominated again for recognition, only if they have provided significant upgrades/improvements, or additional accessible provisions to enhance the accessibility of their architectural features and facilities for PWDs, within the last 2 years, or after they have been previously awarded.

These nominated establishments or building/facilities previously awarded will be required to comply with the same submittal as required to first time nominees. These are Standards and Dimensions, Floor Plans or Site Development Plans, Locations of Accessible Facilities, Supplemental Photos for each accessible features and facilities, Submission of Actual detailed dimensions, and a narrative about the establishment.

Special Awards

For other types of facilities not included in Rule III of BP 344, although its facilities or travel web network is evaluated to be fully accessible to PWDs, will also be given a special recognition award. These travel web network facilities may be classified as:

- 1. Accessible Pedestrian Sidewalk/Roadway Network, where an accessible route/routes will connect to a network of accessible locators, accessible buildings, and/or accessible facilities, within the development or community. Additional credits will be given if audible pedestrian traffic signals are installed throughout the accessible route network.
- 2. PWD Friendly Transportation/Mobility Network including accessible transportation terminal facilities with accessible connecting walkways/routes, leading to accessible transportation vehicle/vehicles. Submittal must include in one package, the following:
 - 2.a) accessible transportation terminal

- 2.b) accessible connecting passageway/walkway/route from the accessible transportation terminal, to the accessible transportation vehicle
- 2.c) accessible transportation vehicle
- 3. Other Type of buildings/facilities or Travel Web/Mobility Network not indicated in Rule III of the IRR of BP 344, although have provided accessible features and facilities for PWDs to be self-reliant, can be nominated for recognition.

Take note that for this section, which is "Other Types of facilities", submittals must show the accessible travel routes starting from an accessible point of origin, to an accessible point of destination, passing through a travel web network of accessible routes. This network must comply to the standards and dimensions indicated in the architectural features and facilities of Rule II of the IRR of bp 344. Submittal includes site development plan or other related plans, showing the flow of the travel web network (accessible map), highlighting the accessible features and facilities along the network. In addition, submittal must include photos of the accessible features and facilities, properly tagged and labeled, with attached schedules of their actual dimensions.

Part II Architectural Features and Facilities criteria include:

- 1. Ramps
 - gradient is 1:12 (maximum)
 - located at/near the main entrance
 - with two (2) handrails at both sides 700mm/900mm
 - maximum length -6.00m (with landing area)
 - width of ramp -1.20m (minimum)
 - location is not dangerous to user
 - a 300mm long extension of the handrail should be provided at the start and end of ramps and stairs [refer to IRR BP 344 for parameters]
- 2. Washrooms and Toilets
 - cubicle dimension (minimum 1.70m X 1.80m)
 - width of door 800mm (minimum)
 - permit easy passage of wheelchair (1.50m turning space)
 - one movable grab bar with 800mm mounting height
 - one fixed to the adjacent wall with 800mm mounting height
 - lavatory with 800mm mounting height and 650mm vertical leg room space
 - center of water closet is 400mm to the finished face of the adjacent wall
 - a 300mm long extension of the handrail should be provided at the start and end of ramps and stairs [refer to IRR BP 344 for parameters]
- 3. Parking Areas/ Stalls

- located at the nearest entrance with signage (@ pavement/upright)
- stall width 3.70m (minimum)

4. Signage (directional and informational signs)

- At toilet, ramp, parking
- Mounting height for toilet door, bottom 1.40m and upper 1.60m
- 2.0m headroom clearance for Protruding wall mounted signage
- UN symbol of accessibility
- Refer to Rule 2 of IRR of BP344 for standards and dimensions
- toilet door signage dimension as 200mm by 200mm

5. Non-skid flooring

- Toilet and ramp floor surfaces with slip-resistant material

6. Doors and entrances

- entrances must be accessible from arrival and departure points to interior lobby
- entrances with vestibules shall be provided a level area with at least 1.80m depth and 1.50m width
- door width 800mm (minimum)
- doorknobs and other hardware located between 820mm 1.06m (900mm preferred)
- door operable by a pressure/ force not more than 4 kg.

7. Stairs

- tread surfaces slip-resistant material
- slanted nosings are preferred than projecting nosings

8. Corridors

- minimum clear width 1.20m
- recesses/turnabout spaces (minimum area 1.50m x 1.50m)
- turnabout spaces must be provided at or within 3.50m of every dead end
- slip-resistant surface/floor finish

9. Elevators

- Must be located not more than 30.00m from the entrance and easily locate with the aid of signage
- shall have a minimum dimension of 1.10m depth x 1.40m width
- control panels and emergency system shall be within reach of a seated person (centerline of topmost buttons shall be 900mm 1.20m from the floor)
- button controls shall be provided with Braille contractions

10. Switches, controls and buzzers

- positioned within 1.20m 1.30m above the floor
- manual switches must be located no farther than 200mm from the latch side of the door

11. Handrails

- Must be installed on both sides of ramps and stairs, and at the outer edges of dropped curbs
- (but not beyond the width of any crossing)
- shall have a diameter dimension of 30mm to 50mm
- handrails attached to walls shall have a clearance of 50mm

12. Drinking Fountain

- one (1) fountain for every 2,000 sq m of floor area or one (1) on each floor
- waterspout shall be at the front and shall be push-button controlled, maximum height 850mm from the floor to the rim

13. Public telephones / ATMs

- clear, unobstructed space of 1.50m x 1.50m infront of a wall-mounted and free-standing units and at alcoves/recesses
- door width 800mm (min.)
- for public telephones, coin slots, dialing controls, receivers and instructional signs shall be located at 1.10m (max.) above the floor
- for ATMs, card slot, cash disbursement slot, botton selectors, and key pad shall be located at 1.10m (max.) above the floor

14. Others

Credits will be given for facilities with one or more of the following awareness programs, or installed features/facilities.

Weight percentage will be based on the extent of how they were provided. Examples are:

- Lowered information counters
- Orientation seminars on assisting PWDs
- Orientation seminars on fire/earthquake evacuation drills for PWDs
- safe area of refuge for PWDs
- audio/visual emergency alarms
- audible pedestrian traffic signals for the visually impaired
- audio/braille/tactile maps
- tactile floor surface for guiding/direction/warning blocks for the visually impaired
 - -provision in company policies re: inclusion of PWDs
- provision on tenant design guidelines requiring strict compliance of BP 344
- other accessible features and facilities not indicated in the IRR of BP344

PWD FRIENDLY ESTABLISHMENT 2013

Apolinario Mabini Awards 2020

I. Nominee Profile		
Establishment Name		
Company Name		
Official Address		
Phone/ Fax		
Website / Email		
SEC registration/ DTI if any:		
Nominated by:		
Position/ relationship to the nominee	2	
Contact Details		
Attachments, if any	Brochure	
	See requirements :	
	Others	
Past Awards received		

*edited May 7, 2019